

ABLE

Intelligent Garment Equipment



Menborn Intelligent Garment Equipment Is Your Best Choice
迈邦智能制衣设备--您的最佳选择!
www.able-mb.com



MENBORN
INTELLIGENT GARMENT EQUIPMENT

About Us

关于迈邦

东莞市迈邦智能制衣设备有限公司是一间专业从事防水衣服设备、无缝制衣设备、热移印设备生产销售厂家。

服务客户群体如: 户外、鞋、帽、箱包、内衣、泳衣、运动等功能性无缝生产厂家
公司目前产品有: 热风机系列、超声波无缝系列、皮带热压无缝系列、冷热压机系列、测试机系列
五大类十多款机型。每一款机型投放市场, 都得到客户的热情支持!

迈邦制衣设备拥有一支一流的经营团队! 从管理、设计、生产、服务都是由丰富行业经验人才担任, 他们热情、高效服务每一个客户! 公司以: “高技术、高投入、高质量”的管理模式, 本着“你的需求, 是我的使命”的服务态度, 携手每一位合作伙伴一同进步!

DONGGUANG MENBORN INTELLIGENT GARMENT EQUIPMENT CO., LTD. is a specialist in manufacturing of waterproof garment machines, sewfree garment machines and thermal pad printing machines. Our serving customers: outdoors, shoes, cap, luggage box, under-wear, swimming suit, sports, etc. functional sewfree manufacture factory. We have many series of product including: hot air sealing machines, ultrasonic sewfree machines, heating belt type sewfree machines, cool and heat press machines, testing machines series. There are totally 5 series now with nearly twenty machine models. Each of them receives good comment and support once put into the market. We have a team of excellent members, with management, design, production and good service staffs. All of them have lots of experience in the related field. They are also have great passion and with high efficiency to serve every customer! The company is upholding the “high technique, high put in, high quality” management model with “your need is our motive” serving attitude and hand in hand with all the partners involved to move forward together.

ABLE

企业文化是企业的动力源泉，迈邦以“人”为核心的企业文化建设，吸取国外先进管理模式，给员工营造一个现代，宽松，人文的工作氛围。迈邦人敢于尝试，求思进，形成了“品质，服务，创新”的企业理念。

Enterprise culture is a source of moving, Menborn using “human” as the core of enterprise culture establishment, using advance foreign management model, which gives the employee a modern, relax and humanity working ambience. People of Menborn have guts to any trial, quest for mind growth and finally transfer to “quality, service and innovation” kind of enterprise idealism.



MH-60

热风机

Hot Air Seam Sealing Machine



特性 / Description:

- 1、上下轮不同速度调节适用于不同弹性物料
 - 2、贴合程序分段（带头，带中，带尾）设置参数更灵活
 - 3、智能送带机构，胶条贴合更平顺，针对弹性物料可灵活控制尺寸
 - 4、复合式风嘴运动轨迹让胶带起头和中间停机过程中，受温更平均，产品更优质
 - 5、全新外观设计，操作空间更广阔
 - 6、PLC编程控制系统，操作简单稳定
- 1、Independent speed control for upper and lower rollers (suiting for different elastic materials).
 - 2、Multiple sealing programs (tape start, middle and ending), provide more convenient operation options.
 - 3、Intelligent tape feeding mechanism makes tape sealing more smooth and pinpoint at elastic fabric elongate problems.
 - 4、Sophisticated X/Y axis complex air nozzle track movement during different sealing process (tape leading, intermittent pause, etc.), provides more even temperature control and better quality.
 - 5、Brilliant outlook and working design provides a broad operating area.
 - 6、PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 3600W	Power Consumption: 3600W
最大速度: 60ft/min	Max. Speed: 60ft/min
风嘴宽度:10-30mm, 标配:22mm	Nozzle Width: 10-30mm, Standard: 22mm
外形尺寸: 1200(L)*655(W)*1700(H)mm	Dimension: 1200(L)*655(W)*1700(H)mm
净重: 110kg	Net Weight: 110kg

MH-61

热风机

Hot Air Seam Sealing Machine



特性 / Description:

- 1、创新上皮带加热设计，停机位无需补压
 - 2、上皮带轮加热有效减少带头、尾打折现象
 - 3、上下轮不同速度调节适用于不同弹性物料
 - 4、贴合程序分段（带头，带中，带尾）设置参数更灵活
 - 5、智能送带机构，胶条贴合更平顺，针对弹性物料可灵活控制尺寸
 - 6、复合式风嘴运动轨迹让胶带起头和中间停机过程中，受温更平均，产品更优质
 - 7、全新外观设计，操作空间更广阔
 - 8、PLC编程控制系统，操作简单稳定
- 1、Innovative upper heating belt design, no need to re-press the parking stand
 - 2、Upper belt heating reduces the tape start and ending folding effectively
 - 3、Independent speed control for upper and lower rollers (suiting for different elastic materials).
 - 4、Multiple sealing programs (tape start, middle and ending), provide more convenient operation options.
 - 5、Intelligent tape feeding mechanism makes tape sealing more smooth and pinpoint at elastic fabric elongate problems.
 - 6、Sophisticated X/Y axis complex air nozzle track movement during different sealing process (tape leading, intermittent pause, etc.), provides more even temperature control and better quality.
 - 7、Brilliant outlook and working design provides a broad operating area.
 - 8、PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 3600W	Power Consumption: 3600W
最大速度: 60ft/min	Max. Speed: 60ft/min
风嘴宽度:10-30mm, 标配 :22mm	Nozzle Width: 10-30mm, Standard: 22mm
外形尺寸: 1200(L)*655(W)*1700(H)mm	Dimension: 1200(L)*655(W)*1700(H)mm
净重: 110kg	Net Weight: 110kg





MH-62

热风机

Hot Air Seam Sealing Machine



特性 / Description:

- 1、上下轮不同速度调节适用于不同弹性物料
 - 2、贴合程序分段（带头，带中，带尾）设置参数更灵活
 - 3、智能送带机构，胶条贴合更平顺，针对弹性物料可灵活控制尺寸
 - 4、单轴风嘴运动轨迹更高效地使胶条贴合，生产效率提高30%
 - 5、PLC编程控制系统，操作简单稳定，软件升级快捷
-
- 1、Independent speed control for upper and lower rollers (suiting for different elastic materials).
 - 2、Multiple sealing programs (tape start, middle and ending), provide more convenient operation options.
 - 3、Intelligent tape feeding mechanism makes tape sealing more smooth and pinpoint at elastic fabric elongate problems.
 - 4、Single axis nozzle track movement is more efficient, Productivity increased by 30%
 - 5、PLC system makes operation more easy and stable, Software upgradeable

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 3600W	Power Consumption: 3600W
最大速度: 60ft/min	Max. Speed: 60ft/min
风嘴宽度:10-30mm, 标配:22mm	Nozzle Width: 10-30mm, Standard: 22mm
外形尺寸: 1200(L)*600(W)*1700(H)mm	Dimension: 1200(L)*600(W)*1700(H)mm
净重: 94kg	Net Weight: 94kg



MU-80

超声波切边贴胶机

Sewfree Tape Lay Down + Ultrasonic Trimming Machine




特性 / Description:

- 1、专属布料参数设定切割程序，应对各种针梳织及超弹性布料都有完美的切割方案
 - 2、针对衣服骨位及重叠变厚位置，机器有加压切割功能
 - 3、智能送带机构，切割裁片与胶条贴合更平顺，针对弹性物料可灵活控制尺寸
 - 4、自主研发自动追频28K静音声波系统，能更轻松切断各种原料，可更换不同型状刀具切出不同形状的花纹
 - 5、带槽及热风双加热设计让切割贴合速度更快，对比上一代提高30%
 - 6、自主研发系统，切刀及焊头坚固耐用
 - 7、上下滚轮独立调节
 - 8、PLC编程控制系统，操作简单稳定
1. Specify parameter program setup, suitable for woven , knit and super elastic fabric in perfect cutting setting
2. Cutting pressure can be adjust according to the thickness of the overlap seam
3. Intelligent tape feeding mechanism makes tape sealing more smooth and pinpoint at elastic fabric elongation problems.
4. Independent development of automatic frequency chasing 28K quiet ultrasonic system, it is easier to cut off various raw materials, Just changing different shape of cutter, it can making many different pattern
5. Tape heating chute and hot air nozzle design increased the adhesive speed up to 30%.
6. Self developed control system makes the cutter and horn much more durable.
7. Independent speed control for upper and lower rollers (suiting for different elastic fabric).
8. PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 3000W	Power Consumption: 3000W
超声波频率: 28 KHz	Ultrasonic Frequency: 28 KHz
外形尺寸: 1200(L)*760(W)*1400(H)mm	Dimension: 1200(L)*760(W)*1400(H)mm
净重: 130kg	Net Weight: 130kg



**MU-81****超声波切边贴胶机****Sewfree Tape Laydown + Ultrasonic Trimming Machine****特性 / Description:**

- 1、专属布料参数设定切割程序，应对各种针梳织及超弹性布料都有完美的切割方案
 - 2、针对衣服骨位及重叠变厚位置，机器有加压切割功能
 - 3、自主研发自动追频20K大功率微噪音声波系统，能更轻松切断各种原料，可更换不同型状刀具切出不同形状的花纹
 - 4、智能送带机械，切割裁片胶条贴合更平顺针对弹性物料可灵活控制尺寸
 - 5、带槽及热风双加热设计让切割贴合速度更快，对比上一代提高30%
 - 6、自主研发系统，切刀及焊头坚固耐用
 - 7、上下滚轮独立调节
 - 8、PLC编程控制系统，操作简单稳定
- 1、Specify parameter program setup, suitable for woven , knit and super elastic fabric in perfect cutting setting
 - 2、Cutting pressure can be adjust according to the thickness of the overlap seam
 - 3、Independent development of automatic frequency chasing 20K high-power but smaller noises ultrasonic system, cutting thick fabric more easily. Just changing different shape of cutter, it can making many different pattern.
 - 4、Intelligent tape dispenser , help cutting the pattern pieces and sticking the adhesive tape more smoothly, the length is easy to control especial for elastic fabric
 - 5、Tape heating chute and hot air nozzle design increased the adhesive speed up to 30%.
 - 6、Our own invention system, making the cutter and horn more durable
 - 7、Independent control setup for upper and lower roller
 - 8、PLC programmable logic control system, making operation more easily and stable

技术参数 / Specifications:

电压 : AC220V 50/60Hz	Power Supply : AC 220V 50/60Hz
气压 : > 0.4 MPa	Air Pressure : > 0.4 MPa
功率 : 3000W	Power Consumption : 3000W Ultrasonic
超声波频率: 20 KHz	Ultrasonic Frequency: 28 KHz
外型尺寸 : 1200(L)*760(W)*1400(H)mm	Dimension : 1200(L)*760(W)*1400(H)mm
净重 : 130kg	Net Weight : 130Kg



MU-82

超声波切边贴胶机

Sewfree Tape Laydown + Ultrasonic Trimming Machine




特性 / Description:

- 1、独特的横臂下轮结构设计，可切袖口、裤脚，夹圈等环状部位
 - 2、专属布料参数设定切割程序，应对各种针梳织及超弹性布料都有完美的切割方案
 - 3、针对衣服骨位及重叠变厚位置，机器有加压切割功能
 - 4、自主研发自动追频28K静音声波系统，能更轻松切断各种原料，可更换不同型状刀具切出不同形状的花纹
 - 5、智能送带机械，切割裁片胶条贴合更平顺针对弹性物料可灵活控制尺寸
 - 6、自主研发系统，切刀及焊头坚固耐用
 - 7、上下滚轮独立调节
 - 8、PLC编程控制系统，操作简单稳定
- 1、Unique side arm structure design, suitable cutting for cuffs, armhole or other annular parts
 - 2、Specify parameter program setup, suitable for woven , knit and super elastic fabric in perfect cutting setting
 - 3、Cutting pressure can be adjust according to the thickness of the overlap seam
 - 4、Independent development of automatic frequency chasing 28K quiet ultrasonic system, it is easier to cut off various raw materials, Just changing different shape of cutter, it can making many different pattern
 - 5、Intelligent tape dispenser, help cutting the pattern pieces and sticking the adhesive tape more smoothly, the length is easy to control especial for elastic fabric
 - 6、Our own invention system, making the cutter and horn more durable
 - 7、Independent control setup for upper and lower roller
 - 8、PLC programmable logic control system, making operation more easily and stable

技术参数 / Specifications:

电压 : AC220V 50/60Hz	Power Supply : AC 220V 50/60Hz
气压 : > 0.4 MPa	Air Pressure : > 0.4 MPa
功率 : 3000W	Power Consumption : 3000W
超声波频率: 28 KHz	Ultrasonic Frequency: 28 KHz
外型尺寸 : 1200(L)*760(W)*1400(H)mm	Dimension : 1200(L)*760(W)*1400(H)mm
淨重 : 115kg	Net Weight : 115Kg




**MU-83****超声波切边贴胶机****Sewfree Tape Laydown + Ultrasonic Trimming Machine****特性 / Description:**

- 1、独特的横臂下轮结构设计，可切袖口、裤脚，夹圈等环状部位
 - 2、专属布料参数设定切割程序，应对各种针梳织及超弹性布料都有完美的切割方案
 - 3、针对衣服骨位及重叠变厚位置，机器有加压切割功能
 - 4、自主研发自动追频28K静音声波系统，能更轻松切断各种原料，可更换不同型状刀具切出不同形状的花纹
 - 5、智能送带机械，切割裁片胶条贴合更平顺针对弹性物料可灵活控制尺寸
 - 6、自主研发系统，切刀及焊头坚固耐用
 - 7、上下滚轮独立调节
 - 8、PLC编程控制系统，操作简单稳定
- 1、Unique side arm structure design, suitable cutting for cuffs, armhole or other annular parts
 - 2、Specify parameter program setup, suitable for woven, knit and super elastic fabric in perfect cutting setting
 - 3、Cutting pressure can be adjust according to the thickness of the overlap seam
 - 4、Independent development of automatic frequency chasing 28K quiet ultrasonic system, it is easier to cut off various raw materials, Just changing different shape of cutter, it can making many different pattern
 - 5、Intelligent tape dispenser, help cutting the pattern pieces and sticking the adhesive tape more smoothly, the length is easy to control especial for elastic fabric
 - 6、Our own invention system, making the cutter and horn more durable
 - 7、Independent control setup for upper and lower roller
 - 8、PLC programmable logic control system, making operation more easily and stable

技术参数 / Specifications:

电压 : AC220V 50/60Hz	Power Supply : AC 220V 50/60Hz
气压 : > 0.4 MPa	Air Pressure : > 0.4 MPa
功率 : 3000W	Power Consumption : 3000W
超声波频率: 20 KHz	Ultrasonic Frequency: 20 KHz
外型尺寸 : 1200(L)*760(W)*1400(H)mm	Dimension : 1200(L)*760(W)*1400(H)mm
淨重 : 118kg	Net Weight : 118Kg



MU-19

手持式超声波机

Handheld ultrasonic machine



特性 / Description:

- 1、自主研发系统，焊头坚固耐用。
 - 2、手持式工作不受任何布种限制灵活运动任何轨迹。
- 1、Independent research and development system, the welding head is sturdy and durable.
2、Handheld work is not restricted by any cloth type and flexible movement of any trajectory.

技术参数 / Specifications:

电压: 220V 50/60HZ

Voltage: 220V 50/60HZ

功率: 1000W

Power: 1000W

超声波频率: 28 KHz

Ultrasonic Frequency: 28 KHz

MC-10

冷热平面压机

Pneumatic Flat Cool +
Heat Press Machine

特性 / Description:

- 1、冷热自动翻转加压工作，提高生产效率，品质更有保障
- 2、独立调节冷热模板压力，应用更灵活
- 3、冷热温度、时间独立可调，自动恒温，温度更精准
- 4、标配工业级冷水机，制冷效果更稳定
- 5、分流式下吸风工作台，吸力更平均
- 6、系统主管模式，设定数据锁定功能方便管理
- 7、PLC控制系统，操作简单稳定

- 1、Heat and cool plates rotate automatically during each pressing cycle, increased both the production efficiency and quality.
- 2、More flexible with Independent pressure control for heat and cool plates.
- 3、Independent heat and cool temperature/timing control with automatic temperature constant control keeps the precise temperature.
- 4、Build-in industrial grade cooling machine gives a more steady temperature control.
- 5、Lower suction platform with multiple air flow chambers provide a more even sucking pressure.
- 6、System administrator control mode provides a more secure and convenient data/parameter setting and locking management.
- 7、PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 3000W	Power Consumption: 3000W
最高设定温度: 250°C	Max. Setting Temp.: 250°C
加压时间: 1-999s	Press Time: 1-999s
发热板面积: 1000(L)*120(W)mm	Heating Plate Area: 1000(L)*120(W)mm
外形尺寸: 1350(L)*850(W)*2200(H)mm	Dimension: 1350(L)*850(W)*2200(H)mm
净重: 425kg	Net Weight: 425kg

MC-12L

平面热压机

Pneumatic Flat Press Machine



选购台架
Option table

特性 / Description:

- 1、标配上下发热、可选择使用上下加热或单热
 - 2、底面加热设计，适合制衣，鞋，箱包，内衣等行业，用途更广泛
 - 3、温度、时间独立可调整，自动恒温温度更精准
 - 4、弹簧自动调整平衡，确保压力平均
 - 5、PLC编程控制系统，操作简单机器更稳定
- 1、Standard self heating upper and lower plates with independent heat on/off control.
 - 2、Double heating design suitable for manufacturing of clothes, shoes, luggage box, underwear etc., provides a wide range of usage.
 - 3、Independent heat and timing control with automatic temperature constant control keeps the precise temperature.
 - 4、Self balance regulating springs give a more even working pressure.
 - 5、PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: 0.3-0.5MPa.	Air Pressure: 0.3-0.5MPa
功率: 5000W	Power Consumption: 5000W
最高设定温度: 250°C	Max. Setting Temp.: 250°C
加压时间: 1-999s	Press Time: 1-999s
发热板面积: 400(L)*400(W)mm	Heating Plate Area: 400(L)*400(W)mm
外形尺寸: 480(L)*800(W)*1580(H)mm	Dimension: 480(L)*800(W)*1580(H)mm
净重: 136kg	Net Weight: 136kg





MC-16

平面热压机

Pneumatic Flat Press Machine



特性 / Description:

- 1、温度、时间独立可调整，自动恒温温度更精准
 - 2、可更换下工作台，方便生产不同形状的部位,应用更广泛
 - 3、弹簧自动调整平衡，确保压力平均
 - 4、PLC编程控制系统，操作简单机器更稳定
-
- 1、Independent heat and timing control with automatic temperature constant control keeps the precise temperature.
 - 2、Exchangeable lower platform for different shape of working parts, provides a wide range of usages.
 - 3、Self balance regulating springs give a more even working pressure.
 - 4、PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: 0.3-0.5MPa.	Air Pressure: 0.3-0.5MPa
功率: 1000W	Power Consumption: 1000W
最高设定温度: 250°C	Max. Setting Temp.: 250°C
加压时间: 1-999s	Press Time: 1-999s
发热板面积: 200(L)*150(W)mm	Heating Plate Area: 200(L)*150(W)mm
外形尺寸: 307(L)*420(W)*1019(H)mm	Dimension: 307(L)*420(W)*1019(H)mm
净重: 45kg	Net Weight: 45kg



MC-17

弧形热压机

Pneumatic Curve Press Machine



特性 / Description:

- 1、弧型发热模具，适合各种弧弯部位压合
- 2、脚踏式随意张紧装置，操作更高效
- 3、悬空式下柱设计更适合袖口、裤脚成品压合
- 4、PLC控制温度、时间

- 1、Curve heating platform, suitable for many small curve position in heat bonding.
- 2、Foot pedal to adjust the tension, make operation more efficiency.
- 3、Suitable for cuff or leg position in heat bonding.
- 4、PLC programmable logic control system for temperature and time.

技术参数 / Specifications:

电压 : AC 220V 50/60Hz	Power Supply : AC 220V 50/60Hz
气压 : 0.3-0.5MPa	Air Pressure : 0.3-0.5MPa
功率 : 700W	Power Consumption : 700W
最高设定温度 : 250°C	Max. Setting Temp. : 250°C
加压时间 : 1-999s	Press Time : 1-999s
发热板面积 : R40*70mm	Heating Plate Area : R40*70mm
外型尺寸 : 1000(L)*500(W)*1750(H)mm	Dimension : 1000(L)*500(W)*1750(H)mm
淨重 : 45kg	Net Weight : 45kg





MC-18

弧形热压机

Pneumatic Curve Press Machine



特性 / Description:

- 1、上发热体及下底座3D特效设计，保证上下弧度完全吻合压力一致均匀。
- 2、可选购下吸风模具。
- 3、标配大，中，小，下工作台模具，可轻松更换。
- 4、安全杆保护装置，安全生产有保证。
- 5、PLC控制系统，确保温度平均精准。

- 1、3D design for upper curve heating mold & lower platform , make the pressure evenly distribute in heat bonding for many small curve position
- 2、Vacuum suction lower platform is available
- 3、Flexible changeable standard 3 size lower platform, make it suitable for different processing
- 4、Reliable safety lever device operate more safety
- 5、PLC programmable logic control system for temperature and time

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply : AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure : > 0.4 MPa
功率: 2400W	Power Consumption :2400W
最高设定温度 : 250°C	Max. Setting Temp. : 250°C
加压时间 : 1-999s	Press Time : 1-999s
发热板面积 : 300(R190mm)*75mm	Heating Plate Area :300(R190mm)*75mm
外型尺寸 : 450(L)*450(W)*1300(H)mm	Dimension : 450(L)*450(W)*1300(H)mm
淨重:59kg	Net Weight :59Kg



MC-20D

平面热压机

Pneumatic Flat Press Machine



选购台架
Option table

特性 / Description:

- 1、双工位移动工作台，生产效率更高
- 2、温度、时间独立可调整，自动恒温温度更精准
- 3、弹簧自动调整平衡，确保压力平均
- 4、PLC编程控制系统，操作简单机器更稳定

- 1、Twin bed change over, more productive
- 2、Independent heat and timing control with automatic temperature constant control keeps the precise temperature.
- 3、Self balance regulating springs give a more even working pressure.
- 4、PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 2500W	Power Consumption: 2500W
最高设定温度: 250°C	Max. Setting Temp.: 250°C
加压时间: 1-999s	Press Time: 1-999s
发热板面积: 600(L)*400(W)mm	Heating Plate Area: 600(L)*400(W)mm
外形尺寸: 1340(L)*870(W)*1580(H)mm	Dimension: 1340(L)*870(W)*1580(H)mm
净重: 170kg	Net Weight: 170kg

MC-20L

平面热压机

Pneumatic Flat Press Machine

选购台架
Option table

特性 / Description:

- 1、标配上下发热、可选择使用上下加热或单热
- 2、底面加热设计，适合制衣，鞋，箱包，内衣等行业，用途更广泛
- 3、温度、时间独立可调整，自动恒温温度更精准
- 4、弹簧自动调整平衡，确保压力平均
- 5、PLC编程控制系统，操作简单机器更稳定

- 1、Standard self heating upper and lower plates with independent heat on/off control.
- 2、Double heating design suitable for manufacturing of clothes, shoes, luggage box, underwear etc., provides a wide range of usage.
- 3、Independent heat and timing control with automatic temperature constant control keeps the precise temperature.
- 4、Self balance regulating springs give a more even working pressure.
- 5、PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 5000W	Power Consumption: 5000W
最高设定温度: 250°C	Max. Setting Temp.: 250°C
加压时间: 1-999s	Press Time: 1-999s
发热板面积: 600(L)*400(W)mm	Heating Plate Area: 600(L)*400(W)mm
外形尺寸: 680(L)*800(W)*1580(H)mm	Dimension: 680(L)*800(W)*1580(H)mm
净重: 156kg	Net Weight: 156kg

MC-21

冷热平压机

Pneumatic Flat Cool + Heat Press Machine



特性 / Description:

- 1、冷热翻转加压模式，生产效率高
- 2、独立冷热温度控制，品质更有保证
- 3、主管模式设计，有效锁定数据
- 4、精准控制温度，压力
- 5、广泛应用于各种热压材料
- 6、标配自动循环冷水机
- 7、可选购工业冷水机

- 1、Automatic exchange for heat and cool plate in one operation, improve the production capacity
- 2、Independent control for heating and cooling temperature
- 3、Supervisor mode locking all the parameter, prevent worker interrupt the operation
- 4、Accuracy control for the temperature and pressure
- 5、Suitable for a range of heat pressing material
- 6、Accompany with industrial grade cooling machine
- 7、Option chiller

技术参数 / Specifications:

电压 : AC220V 50/60Hz	Power Supply : AC220V 50/60Hz
气压 : > 0.4 MPa	Air Pressure : > 0.4 MPa
功率 : 1200W	Power Consumption : 1200W
最高设定温度 : 250°C	Max. Setting Temp. : 250°C
加压时间 : 1-999s	Press Time : 1-999s
发热板面积 : 400(L)*95(W)mm	Heating Plate Area : 400(L)*95(W)mm
外型尺寸 : 640(L)*440(W)*1170(H)mm	Dimension : 640(L)*440(W)*1170(H)mm
净重 : 65kg	Net Weight : 65kg





MC-32X

平面热压机

Pneumatic Flat Press Machine



特性 / Description:

- 1、温度、时间独立可调，自动恒温，温度更精准
 - 2、分流式下吸风工作台，吸力更平均
 - 3、系统主管模式，设定数据锁定功能方便管理
 - 4、PLC控制系统，操作简单稳定
 - 5、可选脚踏控制模式
- 1、Independent heat temperature/timing control with automatic temperature constant control keeps the precise temperature.
- 2、Lower suction platform with multiple air flow chambers provide a more even sucking pressure.
- 3、System administrator control mode provides a more secure and convenient data/parameter setting and locking management.
- 4、PLC programming control system makes operation more easy and stable.
- 5、Selectable Foot Pedal Activation

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 4400W	Power Consumption: 4400W
最高设定温度: 250°C	Max. Setting Temp.: 250°C
加压时间: 1-999s	Press Time: 1-999s
发热板面积: 900(L)*250(W)mm	Heating Plate Area: 900(L)*250(W)mm
外形尺寸: 970(L)*850(W)*2200(H)mm	Dimension: 970(L)*850(W)*2200(H)mm
净重: 175kg	Net Weight: 175kg



MC-37

冷热平压机

Pneumatic Flat Cool + Heat Press Machine



选购冷水机
Option chiller



特性 / Description:

- 1、冷热翻转加压模式，生产效率高
- 2、独立冷热温度控制，品质更有保证
- 3、主管模式设计，有效锁定数据
- 4、精准控制温度，压力
- 5、多种下模形式可选
- 6、标配自动循环冷水机
- 7、可选购工业冷水机

- 1、Automatic exchange for heat and cool plate in one operation, improve the production capacity
- 2、Independent control for heating and cooling temperature
- 3、Supervisor mode locking all the parameter, prevent worker interrupt the operation
- 4、Accuracy control for the temperature and pressure
- 5、Option multi lower mould
- 6、Accompany with industrial grade cooling machine
- 7、Option chiller

技术参数 / Specifications:

电压 : AC220V 50/60Hz	Power Supply : AC220V 50/60Hz
气压 : > 0.4 MPa	Air Pressure : > 0.4 MPa
功率 : 4200W	Power Consumption : 4200W
最高设定温度 : 250°C	Max. Setting Temp. : 250°C
加压时间 : 1-999s	Press Time : 1-999s
发热板面积 : 800(L)*400(W)mm	Heating Plate Area : 800(L)*400(W)mm
外型尺寸 : 1080(L)*600(W)*1700(H)mm	Dimension : 1080(L)*600(W)*1700(H)mm
淨重 : 165kg	Net Weight : 165kg



**MC-40****冷热平压机****Pneumatic Flat Cool + Heat Press Machine****特性 / Description:**

- 1、PLC触屏控制温度、时间、温度更精准。
 - 2、独立调节冷热板压力，压力更平均。
 - 3、标配工业级冷水机，制冷效果更稳定。
 - 4、可选发热底坐，适合厚料压烫。
 - 5、上热板，冷板可旋转工作。
-
- 1、Heat and press time can be adjusted independently. Heat auto control system will keep the machine running on accurate setting temperature.
 - 2、Independent adjusting pressing plate which can provide well-distributed pressure.
 - 3、Comes with industrial chiller.
 - 4、Optional components for heating lower working platform, suitable for thick materials.
 - 5、Hot + Cold upper press plate makes better quality products

技术参数 / Specifications:

电压 : AC220V 50/60Hz	Power Supply : AC220V 50/60Hz
气压 : > 0.4 MPa	Air Pressure : > 0.4 MPa
功率 : 1600W	Power Consumption : 1600W
最高设定温度 : 250°C	Max. Setting Temp. : 250°C
加压时间 : 1-999s	Press Time : 1-999s
发热板面积 : 320(L)*190(W)mm	Heating Plate Area : 320(L)*190(W)mm
外型尺寸 : 718(L)*940(W)*835(H)mm	Dimension : 718(L)*940(W)*835(H)mm
淨重 : 92kg	Net Weight : 92kg



MG-52

自动回转冷热平压机

Pneumatic Heat + Cool Continuous Press Machine



特性 / Description:

- 1、触屏式PLC控制
- 2、全自动连续式皮带输送模式，节省人力，增加产能，一人可同时操作1~3台机
- 3、前热后冷同时加压模式，节省工作时间
- 4、大功率工业级循环制冷效果稳定
- 5、PLC控制加热温度，加压时间，温度时间更精确
- 6、上下发热，上下制冷，广泛适合更多布料和工艺
- 7、整机可快速移动，方便区域排产所需
1. 7 Inch Color Touch Screen Control Panel
2. Standard upper and lower heating plates and upper and lower cooling plates.
3. Continuous multi-station bonding, efficient and firm.
4. Integral lifting and uploading platform, convenient and fast.
5. Software Upgradable
6. Digital Pressure and Temperature Interlock
7. PLC programming control system makes operation more easy and stable
8. Heat and cool plates automatically during each pressing cycle, increased both the production efficiency and quality.

技术参数 / Specifications:

电压 : 380V-3P 50/60Hz	Power Supply: AC 380V-3P 50/60Hz
功率 : 18Kw	Heater Power: 18Kw
最高温度 : 260°C	Maximum Temperature: 260 °C
气缸尺寸φ: 160mm *2	Cylinder Size φ: 160mm *2
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
加压时间: 1-999 s	Timing Range: 1-999 s
发热面积: 920 x 720 mm *2	Upper molds : 920 x 720 mm *2
冷板面积: 920 x 720 mm *2	Upper molds : 920 x 720 mm *2
外型尺寸: 2930(L)*1620(W)*1800(H)mm	Dimension: 2930(L)*1620(W)*1800(H)mm
净重: 1050kg	Net Weight: 1050kg





MA-03

全自动热转印机

Automatic Pick & Place Label Heat Press Machine



特性 / Description:

- 1、自动标签搬运，杜绝人工误差，精确度100%
 - 2、减少压合时、人工摆放标签时间，提升工作效率
 - 3、双PLC一体机独立控制，设定更高效快捷
 - 4、精准控制温度，压力
 - 5、可选脚踏控制模式
-
- 1、Automated Label Handling, Eliminate artificial errors, with 100% accuracy
 - 2、Reduce labeling time during pressing and manual placement, and improve work efficiency.
 - 3、Independent control of dual PLC all-in-one machines, setting more efficient and quicker
 - 4、Independent control for heating and cooling temperature
 - 5、Selectable Foot Pedal Activation

技术参数 / Specifications:

电压 : AC220V 50/60Hz	Power Supply : AC220V 50/60Hz
气压 : > 0.4 MPa	Air Pressure : > 0.4 MPa
功率 : 1200W	Power Consumption : 1200W
最高设定温度 : 250 C	Max. Setting Temp. : 250 C
加压时间 : 1-999s	Press Time : 1-999s
发热板面积 : 200(L)*150(W)mm	Heating Plate Area : 200(L)*150(W)mm
外型尺寸 : 800(L)*440(W)*1170(H)mm	Dimension : 800(L)*440(W)*1170(H)mm
净重 : 55kg	Net Weight : 55kg



AB737-02A

冷切贴胶机

Sewfree Lay Down + Trimmer Machine




特性 / Description:

- 1、高速刀冷切，加热式皮带配合热风，用于贴合双面胶和装饰膜
 - 2、上下加压皮带速度独立调节，适应不同弹性的物料
 - 3、热风和带槽温度独立调节应用更广
 - 4、皮带压力可调节
 - 5、PLC编程控制系统，操作简单机器更稳定
- 1、High speed cold cutting with heating driving belt and hot air nozzle blowing, suitable for double adhesive tape and decoration film.
 - 2、Independent speed control for upper and lower pressure belts, adapts to different elastic materials.
 - 3、Independent temperature control for hot air blowing and heating channel provides a wide range of usage.
 - 4、Adjustable belts pressure.
 - 5、PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 1200W	Power Consumption: 1200W
外形尺寸: 1200(L)*720(W)*1270(H)mm	Dimension: 1200(L)*720(W)*1270(H)mm
净重: 85kg	Net Weight: 85kg



**AB737-03N1****拼贴机****Collage Bonding Machine****特性 / Description:**

- 1、上下皮带分开独立调节速度和温度
 - 2、吹风独立调节风量和温度
 - 3、发热槽独立调节温度
 - 4、皮带压力可调节
 - 5、可另选购多种配件或装置配合生产
 - 6、PLC编程控制系统，操作简单稳定
- 1. Upper and lower belts adjust the speed & temperature separately
 - 2. Blowing adjust air flow and temperature separately
 - 3. Independent adjustment for heating tank temperature
 - 4. Belt pressure is adjustable
 - 5. More options on variety of accessories and devices for production requirement•
 - 6. PLC•programming•control•system•makes•operation•more•easy•and•stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 4100W	Power Consumption: 4100W
最高设定温度: 300°C	Max. Setting Temp.: 300°C
发热板面积(皮带): 70*20mm	Heating Area(belt): 70*20mm
外形尺寸: 1330(L)*660(W)*1380(H)mm	Dimension: 1330(L)*660(W)*1380(H)mm
净重: 95kg	Net Weight: 95kg



AB737-06

埋拼机

Flat Seamer Machine



特性 / Description:

- 1、加长上下皮带装置，热压产品更牢固
 - 2、上下差速送料, 适合多面弹性布料
 - 3、后抬皮带新型设计, 灵活转弯
 - 4、发热槽吹风加热, 有效提升产能
 - 5、可拆装平台, 使用更灵活
- 1、Extra long upper & lower heating belts make heat pressing product more fasten.
- 2、Independent speed control for upper and lower belts (suiting for many different elastic fabric).
- 3、Independent lift up the end position of heating belt, make pattern fabric easy to turn around.
- 4、Tape heating channel plus hot air blowing pipe design increased the adhesive speed and increase the working capacity.
- 5、Detachable platform make it more flexible .

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 3000W	Power Consumption: 3000W
最高设定温度: 300°C	Max. Setting Temp.: 300°C
发热板面积(皮带): 150*15mm	Heating Area(belt): 150*15mm
外形尺寸: 1200(L)*550(W)*1300(H)mm	Dimension: 1200(L)*550(W)*1300(H)mm
净重: 180kg	Net Weight: 180kg

AB737-12B

切边贴胶机

Sewfree Lay Down + Trimmer Machine




特性 / Description:

- 1、袖口，裤脚无缝首选机器
 - 2、高速刀冷切，配合热风和热轮，用于贴合双面胶和装饰膜
 - 3、上下压轮速度、压力可独立调节，适合不同弹性的物料
 - 4、热风和带槽温度独立调节应用更广
 - 5、PLC编程控制系统，操作简单机器更稳定
-
- 1、First choice for sewfree tape lay down of cuff and trouser legs.
 - 2、High speed cold cutting with heating roller and hot air nozzle blowing, suitable for double adhesive tape and decoration film.
 - 3、Independent speed control for upper and lower pressure roller, adapts to different elastic materials.
 - 4、Independent temperature control for hot air blowing and heating channel provides a wide range of usage.
 - 5、PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 1800W	Power Consumption: 1800W
外形尺寸: 1200(L)*550(W)*1230(H)mm	Dimension: 1200(L)*550(W)*1230(H)mm
净重: 90kg	Net Weight: 90kg



AB737-13B

套贴机

Collage Machine



特性 / Description:

- 1、热压双面胶、补强带、折边，可转小弯
 - 2、可转换工作平台（平台及筒式）
 - 3、上下轮速度独立调节适应不同弹性物料
 - 4、热风和带槽温度可独立调节，应用更广
 - 5、PLC编程控制系统，操作简单机器更稳定
-
- 1、Heat press for double adhesive tape, reinforcement tape and folding, can turn a small bend.
 - 2、Exchangable working platforms (flat and circular shape).
 - 3、Independent speed control for upper and lower pressure roller, adapts to different elastic materials.
 - 4、Independent temperature control for hot air blowing and heating channel provides a wide range of usage.
 - 5、PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 1800W	Power Consumption: 1800W
外形尺寸: 1200(L)*720(W)*1270(H)mm	Dimension: 1200(L)*720(W)*1270(H)mm
净重: 85kg	Net Weight: 85kg





AB737-15A

包边机

Binding Machine



特性 / Description:

- 1、皮带连续加压，产品受温更平均，避免分段加压产生的压痕及色差，品质更完美，效率更高
- 2、上下皮带速度、温度及压力独立调节，适用于不同弹性物料
- 3、热风附助吹带，包边牢固美观，不用再补压，有效提高产能
- 4、智能送带机构，产品贴合更平顺，针对弹性物料可灵活控制尺寸
- 5、分段式差速控制，灵活应对多段弹性部位
- 6、PLC编程控制系统，操作简单机器更稳定

- 1、Constant and continuous belt pressure, provide a even working temperature and avoid the colour changes/folding marks between intermittent pause.
- 2、Independent speed control for upper and lower pressure belts, adapts to different elastic materials.
- 3、Additional hot air blowing to the tape, make glue dissolve and stick on the fabric more fasten and no need to repress it, increase the working efficiency.
- 4、Intelligent tape feeding mechanism makes tape sealing more smooth and pinpoint at elastic fabric elongate problems.
- 5、Multi-phase differential speed control, solving the problems of fabric with different elastic rate on the same fabric.
- 6、PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 4500W	Power Consumption: 4500W
外形尺寸: 1200(L)*550(W)*1350(H)mm	Dimension: 1200(L)*550(W)*1350(H)mm
净重: 100kg	Net Weight: 100kg



AB737-900

粘合机

Continuous Pressure Fusing Machine



特性 / Description:

- 1、采用自动纠偏系统，确保上下带不偏离
- 2、采用进口材质无缝皮带，更耐用，粘合布料更平滑
- 3、配置十二组特殊发热板，两段式加热系统，任意设定前段或后段的发热板温度，使热溶区内所需温度控制更精确
- 4、压力滚筒采用耐高温进口材质硅胶包裹，以气缸加压方式，使粘合压力更稳定，从而达到最佳粘合效果
- 5、配有强力抽风冷却系统，让粘合的布料在短时间内降温定型，使粘合效果更理想

- 1、Equipped with automatic conveyor belt alignment system, ensuring the upper and lower conveyor belts are not easy to be deviated and more durability.
- 2、Using imported seamless conveyor belt, much durable and smooth in fusing
- 3、Equipped with 12 sets special heating plates located in front and back two heating zones in which temperatures can be set independently and precisely..
- 4、Using large high temperature silicon coated pressure roller driven by air cylinder to achieve the best laminate effect by its stable pressure..
- 5、Equipped with strong exhausted fan as cooling system, ensure the fusing fabric to be cooled down immediately with the best effect.

技术参数 / Specifications:

电压: 380V/50Hz	Power Supply: 380V/50Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
电热功率: 26KW	Heating Power: 26KW
马达功率: 1KW	Motor Power: 1KW
粘合宽度: 900mm	Fusing Width : 900mm
温度设定: 25~200°C	Temperature: 25~200°C
外形尺寸: 3200(L)*1420(W)*1260(H)mm	Dimension: 3200(L)*1420(W)*1260(H)mm
净重: 800kg	Net Weight: 800kg
最大工作速度: 14m/min	Max speed: 14m/min



MT-91

气动水压测试机

Pneumatic Hydrostatic Tester



特性 / Description:

- 1、触屏式PLC控制
- 2、气动自动开合测试平台，有效提高工作效率
- 3、电子加仪表校正压力，最高可测试30Psi压力
- 4、斜式测试平台，循环水供应系统，干净环保
- 5、自动计时器
- 6、适用于所有动态耐水压测试

- 1、Touch screen PLC programmable logic control system
- 2、Automatic pneumatic drive pump, improve working efficiency
- 3、Basic pressure gauge and digital control the pressure up to 30psi
- 4、Slant test platform, recycling water supply , eco-friendly
- 5、Automatic timer
- 6、Suitable for a range of hydrostatic pressure testing

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
功率: 500W	Power Consumption: 500W
气压: > 0.4 MPa	Air Pressure : > 0.4 MPa
最大测试压力: 28 PSI	Max. Test Pressure: 28 PSI
加压时间: 1-999s	Pressure Holding Time : 1-999s
外形尺寸: 600(L)*500(W)*1200(H)mm	Dimension: 600(L)*500(W)*1200(H)mm
净重: 65kg	Net Weight: 65kg

MT-92
水压测试机
Hydrostatic Tester



特性 / Description:

- 1、数码自动定时器控制
- 2、倾斜式测试平台测试更精准
- 3、可调压力加减阀，适应更广
- 4、压力实时读取
- 5、不锈钢循环水箱，环保，坚固耐用

- 1、Digital automatic timer control
- 2、Oblique test platform to ensure that test range more accuracy
- 3、Adjustable pressure gauge, more flexible
- 4、Real- time pressure reading
- 5、Stainless steel recycle tank, eco and durable

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
功率: 300W	Power Consumption: 300W
最大测试压力: 7 PSI	Max. Test Pressure: 7 PSI
加压时间: 1-999s	Pressure Holding Time : 1-999s
外形尺寸: 1000(L)*500(W)*1300(H)mm	Dimension: 1000(L)*500(W)*1300(H)mm
净重: 40kg	Net Weight: 40kg



MT-93

数显水压测试机
Digital Hydrostatic Tester

特性 / Description:

- 1、数码自动定时器控制
 - 2、倾斜式测试平台测试更精准
 - 3、可调压力加减阀，适应更广
 - 4、数显压力表，两种压力单位显示实时读取
 - 5、不锈钢循环水箱，环保，坚固耐用
-
- 1、Digital automatic timer control
 - 2、Oblique test platform to ensure that test range more accuracy
 - 3、Adjustable pressure gauge, more flexible
 - 4、Duo Digital Real-time pressure reading
 - 5、Stainless steel recycle tank, eco and durable

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
功率: 500W	Power Consumption: 500W
最大测试压力: 14 PSI	Max. Pressure: 14 PSI
加压时间: 1-999s	Pressure Holding Time: 1-999s
外形尺寸: 1000(L)*500(W)*1300(H)mm	Dimension: 1000(L)*500(W)*1300(H)mm
净重: 40kg	Net Weight: 40kg

**HB-01**

定位烫斗
Spotting Iron

**HB-02**

可调温定位烫斗
Temperature-adjustable Spotting Iron





迈邦智能制衣设备
MENBORN INTELLIGENT GARMENT EQUIPMENT

东莞市迈邦智能制衣设备有限公司

DONGGUAN MENBORN INTELLIGENT GARMENT EQUIPMENT CO., LTD.

地址：广东省东莞市高埗镇塘厦村创富街11号

No.11 Chuangfu Street, Tangxia Village, Gaobu Town, Dongguan, Guangdong

TEL: +86 769-86881887 Http://www.able-mb.com

E-mail: sales@able-mb.com

VER 5.0 March 2023



官方网站



微信公众号

