

# DL3880 SERIES

## CHAINSTITCH SEWING MACHINE



DL	388	3	R	H	-	64	P															
<b>機種別</b> Model DL 直驅型 Direct-drive type	<b>針數</b> Number of needles 1 單針 Single Needle 2 雙針 Two Needles 3 三針 Three Needles		<b>針向</b> Needle array - (雙針)橫列 (Two Needles)Parallel R (雙針)縱列 (Two Needles)Tandem - (三針)斜三針* (Three Needles)Oblique R (三針)三角針* (Three Needles)Triangular *註 Remark : 	<b>車縫布料</b> Sewing fabric - 中厚料 Medium H 厚料 Heavy	 <table border="1"> <thead> <tr> <th>No.</th> <th>mm</th> <th>inch</th> </tr> </thead> <tbody> <tr> <td>32</td> <td>3.2</td> <td>1/8"</td> </tr> <tr> <td>48</td> <td>4.8</td> <td>3/16"</td> </tr> <tr> <td>64</td> <td>6.4</td> <td>1/4"</td> </tr> <tr> <td>95</td> <td>9.5</td> <td>3/8"</td> </tr> </tbody> </table>		No.	mm	inch	32	3.2	1/8"	48	4.8	3/16"	64	6.4	1/4"	95	9.5	3/8"	<b>後拖輪</b> Rear puller - 無 None P 平膠拖輪 Rubber wheel G 齒型膠輪 Plastic gear I 齒型鐵輪 Iron gear AP 氣動拖輪 Pneumatic Puller
No.	mm	inch																				
32	3.2	1/8"																				
48	4.8	3/16"																				
64	6.4	1/4"																				
95	9.5	3/8"																				

### 產品特點：

- 一、彎針機構採用的是傾斜彎曲體型的裝置，能發揮優越的耐久性。
- 二、加固縫是與平縫機相同都可通過反縫拉桿進行操作，可確實的防止脫線。
- 三、可對縫跡長度進行簡單的調節。
- 四、帶拖輪裝置，拉料更順暢，縫跡更加平整。



### Features

1. The looper mechanism adopts an obliquely curved body type device, which exhibits excellent durability.
2. The bartack function is the same as the lockstitch machine, which can be operated by the reverse stitching lever, which can definitely prevent thread release.
3. The stitch length can be easily adjusted.
4. The puller device makes the cloth feeding smoother and the stitch forms more flat.

## 規格

## SPECIFICATIONS

DL3880	 mm	 Needle NO.	 mm	 mm	 S.P.M. (Max)	選配 Option		
						後拉輪 Rear Puller	桌板 Table	
DL3881	-	TVx7 #14~#21	2	Min: 1.4 mm Max: 4 mm	8~10mm	3500	-P -G -I -AP	DL7000T-T1
DL3882(H)	3.2 / 4.8 / 6.4 / 9.5	or	4					
DL3882R	-		6					
DL3883(H)	6.4	UY128GAS #14~#20						
DL3883R(H)	6.4							