

ONE NEEDLE LOCKSTITCH MACHINE

DL7200C

-

B

M

1

A

-

16

機種別 Model

DL720 直驅單定針平縫車
Direct-Drive
Needle Positioning
Lockstitch Machine

DL7200C 單步進電腦平縫車
Computerized
Lockstitch Sewing
Machine with
Single Stepping
Motor

DL7200D 雙步進電腦平縫車
Computerized
Lockstitch Sewing
Machine with
Double Stepping
Motor

DL7500 雙步進電腦觸控平縫車
Computerized
Lockstitch Sewing
Machine with
Double Stepping
Motor and Touch
Panel

旋梭 Hook

- 1 高速縫梭頭
High Speed Hook
- 2 大旋梭
Large Hook

送布牙 Feed Dog

- 四排牙
4 Rows of Teeth



A 三排牙
3 Rows of Teeth



功能選配 Function Option

功能碼 Function	快速倒縫 Reverse Feeding	撥線桿 Wiper	電子夾線 Thread Gripper	自動抬壓腳 Auto Lifter	防鳥巢 Bird Nest Prevention	自動切線 Auto Trimming
10	-	-	-	-	-	√
11	√	√	-	-	-	√
12	√	-	-	√	-	√
13	√	√	-	√	-	√
15	√	-	√	-	-	√
16	√	-	√	√	-	√
17	√	-	√	√	√	√

特性 Features

- R 右切刀
Vertical Edge
Trimmer
- B 旋轉式切線系統
Rotary Thread
Trimming
- N 針送布
Needle Feed
- RN 右切刀針送布
Edge Cutter &
Needle Feed

車縫布料 Sewing Material

- L 薄布料
Light
- M 中厚布料
Medium
- H 厚布料
Heavy
- HM 中厚至厚布料
Medium & Heavy
- X 牛仔料
Jeans

DL720 SERIES FEATURES




DL720 直驅單定針平縫車 Direct-Drive Needle Positioning Lockstitch Machine

- 機電一體化的完美整合，內置電控箱及控制台，安裝簡易，使用方便。
- 直驅伺服馬達，反應快速，動作精準，比離合器馬達省電 60%。
- 使用方便：配備 LED 照明，內置式繞線器與補針功能。
- Mechatronic integration with built-in control box and control panel. It is easy to install and operate.
- Direct-drive servo motor is speedy, accurate, and energy-saving than clutch motor by 60%.
- User friendly: Equipped with LED light, built-in bobbin winder, and stitch compensation function.

DL720	mm	Needle No. DB × 1	布料厚度 Fabric Weight			mm		mm	S.P.M. (Max)
			L	M	H	手動 Hand	膝動 Knee		
M1	15.8	#11~#14						0~4	4000
H1	18.0	#18~#21				5.5	13	0~5	3500
M1A	15.8	#11~#14						0~6.5	4000

DL720 -RM1 直驅單定針帶刀平縫車 Direct-Drive Needle Positioning Lockstitch Machine & Edge Cutter




30mm 落料空間：
廢料從落料口自然滑落，每時每刻保持清爽乾淨。

30mm space:
30mm space for giving up the waste, it brings out with a clean working space.



黑金剛鍍層：
刀架導杆均採用 DLC 塗層處理，更耐用更耐磨。

Special black coating:
Cutter's stick is made with DLC coating which helps to increase durability.



簡易定針型可搭配喇叭組，進行布條滾邊車縫（喇叭為三折捲，入布寬度 28mm，出布寬度 8~10mm）

Needle position function models can equip with binders, to perform tape binding. (Binders are with 3 folders; entering width is 28mm, exiting width is 8~10mm for material.)

DL720	mm	mm	Needle No. DB × 1	布料厚度 Fabric Weight			mm		mm	S.P.M. (Max)	mm	KG
				L	M	H	手動 Hand	膝動 Knee				
RM1-32	3.2	15.8	#11~#14						0~4	3700	L630 W245 H540	34.5 / 37.5
RM1-48	4.8						4	10~13 (可調 Adjustable)				
RM1-64	6.4											

※ 選配桌板: DL7000T-T1 ※ Optional Table: DL7000T-T1