



C830/C833 TROUGH IRONING MACHINE



GSB-3000/GSB-3300 FEEDING MACHINE

- The belt conveyor belt enhances the adsorption force of the grass on the conveyor belt, so that the grass is more flat to adsorb on the conveyor belt;
- The sliding window door makes it easier to clean the debris in the suction chamber.
- Feeding speed could be adjustable, which could match ironing speeding easily.
- Efficient suction function, can make cloth grass tail section completely shaking, the use of different linen demand.

Item	Unit	OC833 (S/H/G) 2	OC833 (S/H/G) 3
Number Of Roller	piece	2	3
Roller Diameter	mm	800	800
Max.width	mm	3300	3300
Width	m/min	0-35	5-50
Steam Consumption	kg/h	385	600
Evaporation	l/h	240	330
Gas	l/min	433	667
Hot Oil	l/min	550	850
Drive Motor Power	kw	11	15
Power Of The Exhaust Motor	kw	2.2	4
Exhaust Volume	m3/h	2160	3240
Diameter Of Exhaust Pipe	mm	200	220
Steam Inlet Diameter	DN (mm)	50	65
Steam Outlet Diameter	DN (mm)	40	50
Hot Oil Inlet Diameter	DN (mm)	50	76

Note: The above specifications are subject to change without notice.

Model	GSB-3000/3300
Okuma Power	1.6KW/2
Transmission Power	0.75KW/1
Feeding Power	0.4KW/1
Dimension(L)	3791mm
Dimension(W)	1150mm
Dimension(H)	1380mm

Note: The above specifications are subject to change without notice.