

MH-60

热风机

Hot Air Seam Sealing Machine



特性 / Description:

- 1、上下轮不同速度调节适用于不同弹性物料
 - 2、贴合程序分段（带头，带中，带尾）设置参数更灵活
 - 3、智能送带机构，胶条贴合更平顺，针对弹性物料可灵活控制尺寸
 - 4、复合式风嘴运动轨迹让胶带起头和中间停机过程中，受温更平均，产品更优质
 - 5、全新外观设计，操作空间更广阔
 - 6、PLC编程控制系统，操作简单稳定
- 1、Independent speed control for upper and lower rollers (suiting for different elastic materials).
 - 2、Multiple sealing programs (tape start, middle and ending), provide more convenient operation options.
 - 3、Intelligent tape feeding mechanism makes tape sealing more smooth and pinpoint at elastic fabric elongate problems.
 - 4、Sophisticated X/Y axis complex air nozzle track movement during different sealing process (tape leading, intermittent pause, etc.), provides more even temperature control and better quality.
 - 5、Brilliant outlook and working design provides a broad operating area.
 - 6、PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 3600W	Power Consumption: 3600W
最大速度: 60ft/min	Max. Speed: 60ft/min
风嘴宽度:10-30mm, 标配 :22mm	Nozzle Width: 10-30mm, Standard: 22mm
外形尺寸: 1200(L)*655(W)*1700(H)mm	Dimension: 1200(L)*655(W)*1700(H)mm
净重: 110kg	Net Weight: 110kg

