

MH-62

热风机

Hot Air Seam Sealing Machine



特性 / Description:

- 1、上下轮不同速度调节适用于不同弹性物料
- 2、贴合程序分段（带头，带中，带尾）设置参数更灵活
- 3、智能送带机构，胶条贴合更平顺，针对弹性物料可灵活控制尺寸
- 4、单轴风嘴运动轨迹更高效地使胶条贴合，生产效率提高30%
- 5、PLC编程控制系统，操作简单稳定，软件升级快捷

- 1、Independent speed control for upper and lower rollers (suiting for different elastic materials).
- 2、Multiple sealing programs (tape start, middle and ending), provide more convenient operation options.
- 3、Intelligent tape feeding mechanism makes tape sealing more smooth and pinpoint at elastic fabric elongate problems.
- 4、Single axis nozzle track movement is more efficient, Productivity increased by 30%
- 5、PLC system makes operation more easy and stable, Software upgradeable

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 3600W	Power Consumption: 3600W
最大速度: 60ft/min	Max. Speed: 60ft/min
风嘴宽度:10-30mm, 标配 :22mm	Nozzle Width: 10-30mm, Standard: 22mm
外形尺寸: 1200(L)*600(W)*1700(H)mm	Dimension: 1200(L)*600(W)*1700(H)mm
净重: 94kg	Net Weight: 94kg

