



特性 / Description:

- 1、专属布料参数设定切割程序,应对各种针梳织及超弹性布料都有完美的切割方案
- 2、针对衣服骨位及重叠变厚位置,机器有加压切割功能
- 3、智能送带机构,切割裁片与胶条贴合更平顺,针对弹性物料可灵活控制尺寸
- 4、自主研发自动追频28K静音声波系统,能更轻松切断各种原料,可更换不同型 状刀具切出不同形状的花纹
- 5、带槽及热风双加热设计让切割贴合速度更快,对比上一代提高30%
- 6、自主研发系统,切刀及焊头坚固耐用
- 7、上下滚轮独立调节
- 8、PLC编程控制系统,操作简单稳定
- 1. Specify parameter program setup, suitable for woven , knit and super elastic fabric in perfect cutting setting
- 2. Cutting pressure can be adjust according to the thickness of the overlap seam
- 3. Intelligent tape feeding mechanism makes tape sealing more smooth and pinpoint at elastic fabric elongation problems.
- 4. Independent development of automatic frequency chasing 28K quiet ultrasonic system, it is easier to cut off various raw materials, Just changing different shape of cutter, it can making many different pattern
- 5. Tape heating chute and hot air nozzle design increased the adhesive speed up to 30%.
- 6. Self developed control system makes the cutter and horn much more durable.
- 7. Independent speed control for upper and lower rollers (suiting for different elastic fabric).
- 8. PLC programming control system makes operation more easy and stable.

技术参数 / Specifications:

电压: AC 220V 50/60Hz	Power Supply: AC 220V 50/60Hz
气压: > 0.4 MPa	Air Pressure: > 0.4 MPa
功率: 3000W	Power Consumption: 3000W
超声波频率:28 KHz	Ultrasonic Frequency: 28 KHz
外形尺寸: 1200(L)*760(W)*1400(H)mm	Dimension: 1200(L)*760(W)*1400(H)mm
净重: 130kg	Net Weight: 130kg

