



SXT SERIES TILT AUTOMATIC WASHING MACHINE

- All Suspended Shocking Absorbing System, successfully and efficiently reduce the shocking, make washing steps reliable and well balanced.
- The whole unit is combined inner drums, outer drums, rotatable lifting bearing system, shock absorbing spring, shock reducer and lifting cylinder and so on.
- Intelligent programmable computer control system with big screen, freely programmable, operator could set flexible.
- For high extraction, there are four speeds depending on different materials. The speed regulating system is controlled by LS inverter, washing speed and extracting can raise promptly, protect the garments and other cloth.

Model	Unit	SXT-100F	SXT-120F	SXT-150F
Rated Capacity	kg	100	120	150
Washing Drum Dimension	mm	Φ1200×820	Φ1300*830	Φ1470*880
Motor Power	kw	7.5	11, 1440r/min	18.5, 1440r/min
Inverter Power	kw	11	15	20
Inlet Of Water	inch	2	2	3
Drain Pipe	mm		150	150
Power Consumption Per Cycle	kw	5.5	8	14
Steam Consumption Per Cycle	kg	< =90	< =160	< =200
Water Consumption	l/kg	< =15	< =15	< =15
Dimension (L*w*h)	mm	1750×1640×2132	2000×2200×2200	2500×2280×2280
Weight	kg	3100	4300	5000

Note: The above specifications are subject to change without notice.



XGQ-F AUTOMATIC WASHING MACHINTE (WASHER EXTRACTOR)

- Fully automatic, microcomputer-controller, freely programmable, 30 possible programmes, operator could set flexible.
- Full suspension shock structure, low shake, low noise, combination of shock absorbers and springs for maximum absorption, need no excessive foundations.
- High quality inverter system, easily realize washing and extracting frequency stepless adjusting.
- Multiple sealing system, oil sealing, water sealing, stainless steel sealing.
- Built-out bearing lubrication, simple operation, convenient maintenance.
- Safety door interlock system, reduce fatigue, misuse and the risk.

Model	Unit	XGQ-30F	XGQ-50F	XGQ-70F	XGQ-100F
Capacity	kg	30	50	70	100
Drum Dimension	mm	Φ905×500	Φ1065×628	Φ1200×600	Φ1200×820
Drum Voluem	l	321	559	678	930
Drum Speed(Wash/hi-extract)r/min		40/750	38/720	38/700	38/650
Voltage	v		220/240/380/415/440		
Motor Power	kw	4	5.5	7.5	7.5
Inverter Power	kw	5.5	7.5	11	11
Hot Water Pipe	inch	1	1 1/4	1 1/2	2
Cold Water Pipe	inch	1	1 1/4	1 1/2	2
Air Pressure	mpa	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6
Dimension Lxwxh	mm	1640×1360×1722	1640×1570×1912	1750×1540×2132	1750×1640×2132
Net Weight	kg	1450	2200	2800	3100

Note: The above specifications are subject to change without notice.